

FORTE

POSTDRIVER

FEATURES

- Heavy 320kg hammer standard
- Hydraulic side tilt
- Hydraulic top link
- 4m Beamtec mast - unique reinforcing technology
- Mega Flow hydraulic system
- Heavy duty post cap with polyethylene insert
- 3pt linkage rear mounted
- Heavy duty base with wide support feet
- Cat 1 & 2 linkage
- Heavy duty side tilt and top link rams



SPECS

The FORTE Postdriver is the range topping postdriver from Fieldmaster.

A heavy duty offset base frame provides extra-low centre of gravity for stability and strength, and maximum penetration depth for driving postes and spikes.

Oversize 3"x1.5" angle adjustment hydraulic cylinders control most angles effortlessly, despite the substantial mast weight and structure.



FORTE POST DRIVER

THE FIELDMASTER POSTRAMMER RANGE - FARMER - FENCER - FORTE

STANDARD SPECIFICATIONS

STD MAST LENGTH	4.0M BEAMTEC
WEIGHT (INCL HAMMER)	605KG
STANDARD HAMMER WEIGHT	320KG
SIDE TILT OPERATION	HYDRAULIC (UPSIZED)
TOP LINK OPERATION	HYDRAULIC (UPSIZED)
LINKAGE MOUNTING	CAT 1 + 2
MOUNTING POSITION	REAR 3PT LINKAGE
HEIGHT UNDER HAMMER (4M)	3700MM
HEIGHT UNDER HAMMER (4.5M)	4200MM
MIN RECOMMENDED PSI(MAX)	1800PSI (3000PSI)
MIN HYD FLOW	18L/MIN (60L/MIN)
SIDE TILT ANGLE (L TO R)	20/20
TOP LINK ANGLE (FWD/BACK)	20/28

OPTIONS

- 4.5M Folding mast
- Side shift hydraulic nudge ram kit
- Hydraulic rock spike and extractor kit
- Hydraulic pilot auger kit
- Extra hyd valve banks
- Closed circuit hyd valve system
- Excavator mounting frame
- Operator safety guard